



NOTE:

- 1.ELECTRICAL PROPERTIES:
 1-1.RATING:100V AC MAX OR 12V DC 2A MAX.
 1-2.CONTACT RESISTANCE:50m Ohm MAX
 1-3.INSULATION RESISTANCE:50M Ohm MIN AT 250V DC.
 1-4.DIELECTRIC WITHSTANDING VOLTAGE:AC 250V AC AT 1 MINUTE.
- 2.MATERIAL:
 2-1.PIN:BRASS.
 2-2.INSULATION: PBT+30%GF ,UL 94V-0.
 2-3.SHELL,NUT:ADC 12.
 2-4.ORING:NBR.
- 3.PLATING:
 3-1.PIN: GOLD PLATED 10u" OVER ALL,
 UNDERPLATED NICKEL 60u" MIN OVER ALL.
 3-2.SHELL,NUT:NICKEL PLATED 100u" MIN OVER ALL.

PARTS LIST

NO.	DESCRIPTION	Q'TY
5	NUT	1
4	ORING	1
3	PIN	10
2	HOUSING	1
1	SHELL	1

REV.	DESCRIPTION	CHANGE BY	APPL. BY	DATE
A	Change Shell	Hulk		12/05/08"

繪圖 DRAW. BY	HULK	日期 DATE	11/06/08"	單位 UNIT	mm	一般公差 TOLERANCE	.x ±0.25 .xx ±0.10	圖樣 SYMBOL	料號 PART NO.	WP-10M2-01	圖號 DWG NO.	QC3708	圖樣 VERSION	A
審核 CHECK. BY	YA	核准 APPL. BY		比例 SCALE	1:1									